

KEMCO LE Flexo Adhesive Primer



Application area

- Acts as an activator for KEMPEROL FALLSTOP in case of work interruptions > 7 d

Features

- Lightfast
- Low viscosity
- Transparent
- Low consumption
- 1 part (single component)
- Ready for use
- Resin base: Polyurethane resin

Container size:

6 x 250 ml bottles in a box
1 l container
5 l canister

Storage

Avoid direct sunlight and frost!

Store in closed original containers in dry rooms at temperatures between +5°C and +25°C.

To achieve the best results, it is recommended to store the product at room temperature for approx. 24 hours prior to use.

Opened containers must be sealed air tight and should be used as soon as possible.

See label for use before date.

Material consumption:

at least 50 ml/m²

Properties

Form	Liquid
Colour	Transparent
Cured after *	approx. 60 min
Recoat after*	approx. 1 h to max. 6 h

* Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

Application

Substrates must be dry, firm and free from contaminants which may affect adhesion and must be prepared accordingly.

Application

Use a cloth to apply the material thinly and evenly to the whole area of the substrate

Personal protective equipment must be worn.

Sufficient ventilation is essential to guarantee full curing. Always adhere to relevant rules and regulations.

For further information on application, please refer to the separate technical data sheets and the application instructions.

Important note

Please refer to the respective safety data sheet for hazard warnings, protective measures, hazardous substance classes and correct disposal!

Disposal

Liquid	EAK 08 04 09
cured	EAK 08 04 10

GISCODE

PU50

General information

The times given above are reduced with higher and increased with lower ambient and substrate temperatures. KEMPER SYSTEM products must not be mixed with other manufacturers' products.

Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEMPER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2019-12-11